




# HD 3/5/8 Series

Medium Duty Foot Switches

## Specifications


	H3N	HD3N	HD3NX	HD3LX	HD5NX	HD202P/301P
Contact	1NO + 1NC			2NO + 2NC		
Regular Voltage	15A 125/250/380VAC					
Built-in Switch	Z type micro switch (CE Certified)					
Body Material	Plastic	Aluminum Die casting				
Cable	1/2 inch tap flexible cable (zinc connector 10~16)					
Degree of Protection	IP65			IP54		

## Contact Diagram




### SWITCH1

BLACK  
YELLOW  
RED



### SWITCH2

BLUE  
ORANGE  
GREEN



⊕ YELLOW · GREEN

## Dimensions

(Unit: mm)

**HRF-H3N**  
200.0 X 100.0 X 125.0  
(Plastic body, CE Only)

**HRF-HD3NS**  
300.0 X 150.0 X 127.0

**HRF-HD3N**  
206.0 X 115.0 X 129.0

**HRF-HD3LX**  
200.0 X 150.0 X 127.0  
Safety Lock Type

**HRF-HD3NX**  
200.0 X 150.0 X 127.0

**HRF-HD202P**  
210.0 X 308.0 X 130.0  
(CE Only)

**HRF-HD5NX**  
240.0 X 236.0 X 143.0

**HRF-HD5NS**  
290.0 X 236.0 X 143.0

- Tower Lights
- Beacon Lights
- LED Indicators Pilot Lamps
- Buzzer Alarms
- Pushbutton Switches
- Limit Switches
- Foot Switches
- SSR
- Relay & Sockets
- Relay Terminal Blocks
- Terminal Blocks
- Fuse Holders
- Enclosures
- H4