

FCGL

Cable Glands



Specifications



Material	High Quality Polyamide 6	Degrees of Protection	IP 68 (EN 60529)
The max. Instantaneous Temperature	-40 °C to +105°C	Short Term	up to +150° C
Self-Extinguishing	UL94-HB / Free of Halogen Phosphorous and cadmium	Color	Black & Gray
Application	Connector for control box radio box or cables from electric machine. Water & Dust, Oil proof halogen free.		

(Unit : mm)

	Ordering No.		Thread	Øi (Min)	Øi (Max)	S	L1	L	ØD	SW1	SW2
	Black	Gray									
PF Thread (JIS B0202)	FCGL-G10B	FCGL-G10G	G1/2"	3.5	6.5	20.9	9.0	37.9	25.4	22.6	18.0
	FCGL-G12B	FCGL-G12G	G1/2"	4.0	8.0	20.9	9.0	40.2	28.8	25.5	21.3
	FCGL-G16B	FCGL-G16G	G1/2"	7.0	12.3	20.9	9.0	41.2	28.6	25.4	25.4
Metric Thread (EN 60423)	FCGL-M10B	FCGL-M10G	M12 X 1.5	3.5	6.5	12.0	9.0	37.9	25.4	22.6	18.0
	FCGL-M120B	FCGL-M120G	M16 X 1.5	3.5	6.5	16.0	9.0	37.9	25.4	22.6	18.0
	FCGL-M102B	FCGL-M102G	M12 X 1.5	4.0	7.1	12.0	9.0	40.2	28.8	25.5	21.3
	FCGL-M12B	FCGL-M12G	M16 X 1.5	4.0	8.0	16.0	9.0	40.2	28.8	25.5	21.3
	FCGL-M162B	FCGL-M162G	M20 X 1.5	4.0	8.0	20.0	9.0	40.2	28.8	25.5	21.3
	FCGL-M126B	FCGL-M126G	M16 X 1.5	7.0	10.9	16.0	9.0	41.2	28.6	25.4	25.4
	FCGL-M16B	FCGL-M16G	M20 X 1.5	7.0	12.3	20.0	9.0	41.2	28.6	25.4	25.4
	FCGL-M216B	FCGL-M216G	M25 X 1.5	7.0	12.3	25.0	9.0	41.2	28.6	25.4	25.4
	Pg Thread (DIN 40430)	FCGL-P09B	FCGL-P09G	Pg09	3.5	6.5	15.2	9.0	37.9	25.4	22.6
FCGL-P092B		FCGL-P092G	Pg09	4.0	8.0	15.2	9.0	40.2	28.8	25.5	21.3
FCGL-P11B		FCGL-P11G	Pg11	4.0	8.0	18.6	9.0	40.2	28.8	25.5	21.3
FCGL-P132B		FCGL-P132G	Pg13.5	4.0	8.0	20.4	9.0	40.2	28.8	25.5	21.3
FCGL-P162B		FCGL-P162G	Pg16	4.0	8.0	22.5	9.0	40.2	28.8	25.5	21.3
FCGL-P116B		FCGL-P116G	Pg11	7.0	12.3	18.6	9.0	41.2	28.6	25.4	25.4
FCGL-P13B		FCGL-P13G	Pg13.5	7.0	12.3	20.4	9.0	41.2	28.6	25.4	25.4
FCGL-P16B		FCGL-P16G	Pg16	7.0	12.3	22.5	9.0	41.2	28.6	25.4	25.4



TICG

Cable Glands

Specifications



Material	High Quality Polyamide 6	Degrees of Protection	IP 68 (EN 60529)
The max. Instantaneous Temperature	-40 °C to +105°C	Short Term	up to +150° C
Self-Extinguishing	UL94-HB / Free of Halogen Phosphorous and cadmium	Color	Black & Gray
Application	Connector for control box radio box or cables from electric machine. Water & Dust, Oil proof halogen free.		

(Unit : mm)

	Ordering No.		Thread	Shell Size	Øi (Min)	Øi (Max)	L1	L	ØO	ØD	SW1	SW2
	Black	Gray										
UNEF Thread (ASME B1.1)	TICG-U1010B	TICG-U1010G	1/2-28UNEF	8S, 10S	3.5	6.5	10.0	43.9	18.4	25.4	22.6	18.0
	TICG-U1210B	TICG-U1210G	5/8-24UNEF	10SL, 12S	3.5	6.5	10.0	43.9	20.6	25.4	22.6	18.0
	TICG-U1410B	TICG-U1410G	3/4-20UNEF	14, 14S	3.5	6.5	10.0	43.9	24.0	25.4	22.6	18.0
	TICG-U1610B	TICG-U1610G	7/8-20UNEF	16, 16S	3.5	6.5	10.0	43.9	28.0	25.4	22.6	18.0
	TICG-U1810B	TICG-U1810G	1-20UNEF	18	3.5	6.5	10.0	43.9	31.0	25.4	22.6	18.0
	TICG-U2010B	TICG-U2010G	1 3/16-18UNEF	20, 22	3.5	6.5	10.0	43.9	35.5	25.4	22.6	18.0
	TICG-U2810B	TICG-U2810G	1 7/16-18UNEF	24, 28	3.5	6.5	10.0	43.9	42.0	25.4	22.6	18.0
	TICG-U1212B	TICG-U1212G	5/8-24UNEF	10SL, 12S	4.0	8.0	10.0	46.2	20.6	28.8	25.5	21.3
	TICG-U1412B	TICG-U1412G	3/4-20UNEF	14, 14S	4.0	8.0	10.0	46.2	24.0	28.8	25.5	21.3
	TICG-U1612B	TICG-U1612G	7/8-20UNEF	16, 16S	4.0	8.0	10.0	46.2	28.0	28.8	25.5	21.3
	TICG-U1812B	TICG-U1812G	1-20UNEF	18	4.0	8.0	10.0	46.2	31.0	28.8	25.5	21.3
	TICG-U2012B	TICG-U2012G	1 3/16-18UNEF	20, 22	4.0	8.0	10.0	46.2	35.5	28.8	25.5	21.3
	TICG-U2812B	TICG-U2812G	1 7/16-18UNEF	24, 28	4.0	8.0	10.0	46.2	42.0	28.8	25.5	21.3
	TICG-U1616B	TICG-U1616G	7/8-20UNEF	16, 16S	7.0	12.3	10.0	47.2	28.0	28.6	25.4	25.4
	TICG-U1816B	TICG-U1816G	1-20UNEF	18	7.0	12.3	10.0	47.2	31.0	28.6	25.4	25.4
	TICG-U2016B	TICG-U2016G	1 3/16-18UNEF	20, 22	7.0	12.3	10.0	47.2	35.5	28.6	25.4	25.4
	TICG-U2816B	TICG-U2816G	1 7/16-18UNEF	24, 28	7.0	12.3	10.0	47.2	42.0	28.6	25.4	25.4
	TICG-U2222B	TICG-U2222G	1 3/16-18UNEF	20, 22	12.0	18.0	10.0	53.4	35.5	38.2	34.0	34.0
	TICG-U2822B	TICG-U2822G	1 7/16-18UNEF	24, 28	12.0	18.0	10.0	53.4	42.0	38.2	34.0	34.0
	TICG-U3222B	TICG-U3222G	1 3/4-18UNS	32	12.0	18.0	10.0	53.4	50.0	38.2	34.0	34.0
	TICG-U3622B	TICG-U3622G	2-18UNS	36	12.0	18.0	10.0	53.4	56.5	38.2	34.0	34.0
	TICG-U3228B	TICG-U3228G	1 3/4-18UNS	32	18.0	26.0	10.0	53.4	50.0	49.0	43.4	43.4
	TICG-U3628B	TICG-U3628G	2-18UNS	36	18.0	26.0	10.0	67.7	56.5	59.0	53.0	51.6
	TICG-U3636B	TICG-U3636G	2-18UNS	36	22.0	33.0	10.0	69.7	56.5	74.0	66.5	67.0