



AGD Series

Dual Door Type Enclosures

- Pre-assembled cover and transparent window
- Built-in hinge and stainless steel latch
- Detachable cover for easy access
- Fiberglass reinforced polycarbonate base



Specifications

Protection Level	IP66(ARD) IP64(AGD)
Certification	CE, TUV, RoHS
Temperature range	ABS: -40°C to 70°C (-40°F to 158°F)
	PC: -40°C to 110°C (-40°F to 230°F)
Flammability Rating	ABS: UL94-HB
	PC: UL94-V-0, 5VA, 94-HB

*The base of Polycarbonate model contains 10% glass fiber for reinforcement

Part Numbers and Size

Models		Size		Back Panels		IP Rating
ABS	PC	mm	inches	Steel 1.6mm +	Plastic 3mm +	
BC-ARD-253517	BC-CRD-253517	250 x 350 x 170	9.84 x 13.78 x 6.69	BC-2535ST	BC-2535P	IP 66
BC-ARD-253519	BC-CRD-253519	250 x 350 x 190	9.84 x 13.78 x 7.48	BC-2535ST	BC-2535P	
BC-AGD-354513	BC-CGD-354513	350 x 450 x 130	13.78 x 17.72 x 5.12	BC-3545ST	BC-3545P	IP 64
BC-AGD-354517	BC-CGD-354517	350 x 450 x 170	13.78 x 17.72 x 6.69	BC-3545ST	BC-3545P	
BC-AGD-354521	BC-CGD-354521	350 x 450 x 210	13.78 x 17.72 x 8.27	BC-3545ST	BC-3545P	

