

PRAW series Ordering Information

PRAW	T	18	-	5	D	N	-	V
------	---	----	---	---	---	---	---	---

Cable type	Blank	Standard cable
	I	IEC Standard
Output	O	Normally Open
	C	Normally Closed
Power	D	DC type : 12-24VDC
Sensing distance	2	For PR12
	5	For PR18
	10	For PR30
Sensing face	12	M12 Housing
	18	M18 Housing
	30	M30 Housing
	T	DC 2 wire type
PRAW	M12 connector w/Cable Spatter resistance type Cylindrical Inductive type	

PRAW series, Spatter-resistance, DC 2 wire, M12 connector w/300mm cable

Housing size (mm)		Sensing distance	Output	Part name
Sensing face	Body Length			
M12	43	2	NO	PRWT12-2DO
			NC	PRWT12-2DC
			NO	PRWT12-2DO-I
			NC	PRWT12-2DC-I
M18	47.5	5	NO	PRWT18-5DO
			NC	PRWT18-5DC
			NO	PRWT18-5DO-I
			NC	PRWT18-5DC-I
M30	58.5	10	NO	PRWT30-10DO
			NC	PRWT30-10DC
			NO	PRWT30-10DO-I
			NC	PRWT30-10DC-I

Note - I : IEC standard (IEC)