


# TVC

## Y Type Connector

### Specifications

Material	High Quality Polyamide 6	Degrees of Protection	IP 67 (EN 60529)
The max. Instantaneous Temperature	-40 °C to +105°C	Short Term	up to +150° C
Self-Extinguishing	UL94-HB / Free of Halogen Phosphorous and cadmium	Color	Black & Gray
Feature	CPS distributors guarantee elegant layout and save on cost instead of using distribution boxes. Nominal width from 28, reduceable to 10.		



(Unit : mm)



Ordering No.		A	B	C	$\phi A$	A1	$\phi B$	B1	$\phi C$	C1	$\phi G$	F	H1	H	L
Black	Gray														
TVC-101010B	TVC-101010G	10	10	10	23	26.6	23	26.6	23	26.6	5.0	24	41.6	86	80.0
TVC-121010B	TVC-121010G	12	10	10	25	26.5	23	26.6	23	26.6	5.0	24	41.5	86	80.0
TVC-121210B	TVC-121210G	12	12	10	25	26.5	25	26.5	23	26.6	5.0	24	41.5	88	83.0
TVC-121212B	TVC-121212G	12	12	12	25	26.5	25	26.5	25	26.5	5.0	24	41.5	88	83.0
TVC-161010B	TVC-161010G	16	10	10	30	28.5	23	26.6	23	26.6	5.0	24	43.5	88	83.0
TVC-161210B	TVC-161210G	16	12	10	30	28.5	25	26.5	23	26.6	5.0	24	43.5	90	81.0
TVC-161212B	TVC-161212G	16	12	12	30	28.5	25	26.5	25	26.5	5.0	24	43.5	90	83.0
TVC-161616B	TVC-161616G	16	16	16	30	28.5	30	28.5	30	28.5	5.0	24	43.5	93	89.8
TVC-222222B	TVC-222222G	22	22	22	41	33.3	41	33.3	41	33.3	5.6	39	48.2	112	112.0
TVC-282222B	TVC-282222G	28	22	22	47	39.0	41	33.3	41	33.3	5.6	39	53.9	118	112.0
TVC-282822B	TVC-282822G	28	28	22	47	39.0	47	39.0	41	33.3	5.6	39	53.9	124	118.0
TVC-282828B	TVC-282828G	28	28	28	47	39.0	47	39.0	47	39.0	5.6	39	53.9	124	124.0

# TYC

## Y Type Connector

### Specifications

Material	High Quality Polyamide 6	Degrees of Protection	IP 67 (EN 60529)
The max. Instantaneous Temperature	-40 °C to +105°C	Short Term	up to +150° C
Self-Extinguishing	UL94-HB / Free of Halogen Phosphorous and cadmium	Color	Transparency
Feature	CPS distributors guarantee elegant layout and save on cost instead of using distribution boxes. Nominal width from 28, reduceable to 10.		



(Unit : mm)

Ordering No.		A	B	C	$\phi A$	A1	$\phi B$	B1	$\phi C$	C1	$\phi G$	F	H1	H	L
Black	Gray														
TYC-101010B	TYC-101010G	10.0	10.0	10.0	23.0	26.6	23.0	24.0	23.0	24.0	5.0	24.0	41.6	104.0	67.0
TYC-121010B	TYC-121010G	12.0	10.0	10.0	25.0	26.5	23.0	24.0	23.0	24.0	5.0	24.0	41.5	104.0	67.0
TYC-121210B	TYC-121210G	12.0	12.0	10.0	25.0	26.5	25.0	24.4	23.0	24.0	5.0	24.0	41.5	107.0	69.7
TYC-121212B	TYC-121212G	12.0	12.0	12.0	25.0	26.5	25.0	24.4	25.0	24.4	5.0	24.0	41.5	107.0	73.5
TYC-161010B	TYC-161010G	16.0	10.0	10.0	30.0	28.5	23.0	24.0	23.0	24.0	5.0	24.0	43.5	105.7	67.0
TYC-161210B	TYC-161210G	16.0	12.0	10.0	30.0	28.5	25.0	24.4	23.0	24.0	5.0	24.0	43.5	108.7	69.7
TYC-161212B	TYC-161212G	16.0	12.0	12.0	30.0	28.5	25.0	24.4	25.0	24.4	5.0	24.0	43.5	108.7	73.0
TYC-161616B	TYC-161616G	16.0	16.0	16.0	30.0	28.5	30.0	26.0	30.0	26.0	5.0	24.0	43.5	110.8	83.0
TYC-222222B	TYC-222222G	22.0	22.0	22.0	41.0	33.3	41.0	33.5	41.0	33.5	5.6	39.0	48.2	134.5	108.0
TYC-282222B	TYC-282222G	28.0	22.0	22.0	47.0	39.0	41.0	33.5	41.0	33.5	5.6	39.0	53.9	142.0	108.0
TYC-282822B	TYC-282822G	28.0	28.0	22.0	47.0	39.0	47.0	39.5	41.0	33.5	5.6	39.0	53.9	150.0	111.0
TYC-282828B	TYC-282828G	28.0	28.0	28.0	47.0	39.0	47.0	39.5	47.0	39.5	5.6	39.0	53.9	150.0	114.0